Structural system XC

Contents

System information 469
Beams XC 470
Beam accessories XC 473
Connectors XC 474
Feet XC 479
Enclosure components XC 483
Enclosure components XC – conduit elements 486
Components for linear motion XC 488
Components for rotating motion XC 490

System information

Features



FlexLink´s structural system XC is based on aluminium beams with T-slots for easy interconnections and attachment of external devices. Beam sizes in the XC system range from 24×24 mm up to 176×88 mm.

The system offers sturdy components which provide high load capacity for both static and linear motion systems. It is used within a wide range of applications, from frameworks, work benches and enclosures to special machinery, pick and place units and gantry robot.

T-slot dimensions

All support beams have holes for M6 screws in the corners for connecting mounting plates, end plates etc. Always use roller threading to ensure a reliable screw connection. The screw holes in the centre of all XCBM beams and XCBL enclosure beams are intended for M8 roller threading or self-tapping screws.



T-slot, standard beam *T-slot, lightweight beam*



T-slot, corner profile *T-slot, small beam*

Beam specifications

Beam type	Cross-section mm^2	Weight kg/m	I_x mm^4 $\times 10^4$	I_y mm^4 $\times 10^4$	W_x mm^3 $\times 10^3$	W_y mm^3 $\times 10^3$
XCBM ..x88×176	3970	10,7	1244	369	141	83,9
XCBM ..x44×176	2633	7,11	750	58,2	85,2	26,5
XCBM ..x88×132	2966	8,01	530	259	80,3	58,9
XCBM ..x44×132	2022	5,34	330	40,0	50,0	18,0
XCBM ..x88	1952	5,27	173		39,4	
XCBL ..x88	1180	3,18	126		28,6	
XCBM ..x44×88	1311	3,54	103	25,6	23,5	11,7
XCBL ..x44×88	886	2,39	81,4	21,6	18,5	9,8
XCBM ..x64	1493	4,27	70,2		22,1	
XCBL ..x64	848	2,29	44,5		14,0	
XCBM ..x44×64	1054	2,84	42,0	23,5	13,2	10,7
XCBL ..x44×64	724	1,96	33,9	17,7	10,6	8,1
XCBM ..x44	767	2,07	14,0		6,3	
XCBL ..x44	588	1,59	12,7		5,8	
XCBL ..x44 T2	615	1,66	12,6	13,1	5,6	5,9
XCBL ..x44 T2A	598	1,61	12,9	12,4	5,8	5,6
XCBL ..x44 T3	653	1,76	12,6	13,4	5,7	6,1
XCBR ..x44	708	1,91	13,2	7,8	4,3	2,9
XCBR ..x49		1,77				
XCBA ..x44	572	1,55	9,47	9,47	3,65	3,65
XCBL ..x15×44	327	0,88	6,8	0,83	3,10	1,10
XCBB ..x24×44	375	1,02	5,55	2,41	2,52	2,00
XCBB ..x24×34	310	0,83	3,85	1,75	2,14	1,46
XCBB ..x24	240	0,64	1,10		0,92	

Lengths and tolerance aluminium beams

"3 m" aluminium beams

If no other tolerance is stated in the catalogue all "3 m" aluminium beams will be delivered with a length of 3030 ±5 mm

The extra length compensates for cut losses on local site.

"L-cut" aluminium beams

If no other range is mentioned in the catalogue L-cut aluminium beams can be ordered in the range of 30-3000 mm.

Length tolerances:

Cut length L (mm)	Length tolerance (mm)
30-1000	±0,3
1001-2000	±0,5
2001-3000	±0,8

Support beams

Support beam 88×176



Beam 88 mm × 176 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×88×176**
Length to order (30- 3000 mm) **XCBM L×88×176**

Beam weight: 10,7 kg/m
End cap: Use XCBE 88 (2)

Support beam 44×176



Beam 44 mm × 176 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×44×176**
Length to order (30- 3000 mm) **XCBM L×44×176**

Beam weight: 7,11 kg/m
End cap: Use XCBE 44×88 (2)

Support beam 88×132



Beam 88 mm × 132 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×88×132**
Length to order (30- 3000 mm) **XCBM L×88×132**

End cap, polyamide **XCBE 88×132 A***

Beam weight: 8,01 kg/m
**Note. Contains 10 pcs.*

 © FlexLink 2026

Support beam 44×132



Beam 44 mm × 132 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×44×132**
Length to order (30- 3000 mm) **XCBM L×44×132**

End cap, polyamide **XCBE 44×132 A***

Beam weight: 5,34 kg/m
**Note. Contains 10 pcs.*

Support beam 44×88



Beam 44 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×44×88**
Length to order (30- 3000 mm) **XCBM L×44×88**

End cap, polyamide **XCBE 44×88***

Beam weight: 3,54 kg/m
**Note. Contains 10 pcs.*

Support beam 88×88



Beam 88 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×88**
Length to order (30- 3000 mm) **XCBM L×88**

End cap, polyamide **XCBE 88***

Beam weight: 5,27 kg/m
**Note. Contains 10 pcs.*

Support beam 44×88, lightweight



Beam 44 mm × 88 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44×88**
Length to order (30- 3000 mm) **XCBL L×44×88**

End cap, polyamide **XCBE 44×88***

Beam weight: 2,39 kg/m
**Note. Contains 10 pcs.*

Support beam 88×88, lightweight



Beam 88 mm × 88 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×88**
Length to order (30- 3000 mm) **XCBL L×88**

End cap, polyamide **XCBE 88***

Beam weight: 3,18 kg/m
**Note. Contains 10 pcs.*

Support beam 64×64



Support beam 64 mm × 64 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×64**
Length to order (30- 3000 mm) **XCBM L×64**

End cap, polyamide **XCBE 64***

Beam weight: 4,27 kg/m
**Note. Contains 10 pcs.*

Support beam 64×64, lightweight



Support beam 64 mm × 64 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×64**
Length to order (30- 3000 mm) **XCBL L×64**

End cap, polyamide **XCBE 64***

Beam weight: 2,29 kg/m
**Note. Contains 10 pcs.*

Support beam 44×64



Support beam 44 mm × 64 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×44×64**
Length to order (30- 3000 mm) **XCBM L×44×64**

End cap, polyamide **XCBE 44×64***

Beam weight: 2,84 kg/m
**Note. Contains 10 pcs.*

Support beam 44×64, lightweight



Support beam 44 mm × 64 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44×64**
Length to order (30- 3000 mm) **XCBL L×44×64**

End cap, polyamide **XCBE 44×64***

Beam weight: 1,96 kg/m
**Note. Contains 10 pcs.*

Support beam 44×44



Support beam 44 mm × 44 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBM 3×44**
Length to order (30- 3000 mm) **XCBM L×44**

End cap, polyamide **XCBE 44***

Beam weight: 2,07 kg/m
**Note. Contains 10 pcs.*

Support beam 44×44, lightweight



Support beam 44 mm × 44 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44**
Length to order (30- 3000 mm) **XCBL L×44**

End cap, polyamide **XCBE 44***

Beam weight: 1,59 kg/m
**Note. Contains 10 pcs.*

Support beam, 45°



Support beam, 45°
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBA 3×44**
Length to order (30- 3000 mm) **XCBA L×44**

End cap, polyamide **XCBE 44 A***

Beam weight: 1,55 kg/m
**Note. Contains 10 pcs.*

Beams for enclosures

FlexLink´s beams for enclosures: see page 483.

 © FlexLink 2026

Small beams

Small beam 15×44



Small beam 15 mm × 44 mm
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×15×44**
Length to order (30- 3000 mm) **XCBL L×15×44**

End cap, polyamide **XCBE 15×44***

Beam weight: 0,88 kg/m
**Note. Contains 10 pcs.*

Small beam 24×44



Small beam 24 mm × 44 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBB 3×24×44**
Length to order (30- 3000 mm) **XCBB L×24×44**

End cap, polyamide **XCBE 24×44***

Beam weight: 1,02 kg/m
**Note. Contains 10 pcs.*

Small beam 24×34



Small beam 24 mm × 34 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBB 3×24×34**
Length to order (30- 3000 mm) **XCBB L×24×34**

End cap, polyamide **XCBE 24×34***

Beam weight: 0,83 kg/m
**Note. Contains 10 pcs.*

Small beam 24×24



Small beam 24 mm × 24 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBB 3×24**
Length to order (30- 3000 mm) **XCBB L×24**

End cap, polyamide **XCBE 24***

Beam weight: 0,64 kg/m
**Note. Contains 10 pcs.*

Beam accessories XC

Cover strip, aluminium



Cover strip
Length 2 m
Aluminium, anodized **XCAC 2**

Note! Can't be used with bends

Cover strip, PVC



Cover strip
Length 3 m
Polyvinyl chloride **XCAC 3 P**

Note! Can't be used with bends

Cover strip for T-slot, PVC



Cover strip for T-slot
Length 25 m
Grey PVC

XCAC 25 P

Connectors XC

Angle bracket, die-cast, 80×80×82



Angle bracket
Aluminium, die-cast

XCFA 88 A

Mounting: M6S 8×16 (8), BRB 8.4×16 (8), XCAN 8 (8)

Angle bracket, die-cast, 42×42×82



Angle bracket
Aluminium, die-cast

XCFA 88 B

Mounting: M6S 8×16 (4), BRB 8.4×16 (4), XCAN 8 (4)

Angle bracket, die-cast, 80×80×38



Angle bracket
Aluminium, die-cast

XCFA 44 A

Mounting: M6S 8×16 (4), BRB 8.4×16 (4), XCAN 8 (4)

Angle bracket, die-cast, 42×42×38



Angle bracket
Aluminium, die-cast

XCFA 44 B

Mounting: M6S 8×16 (2), BRB 8.4×16 (2), XCAN 8 (2)

Angle bracket, die-cast, 80×42×38



Angle bracket
Aluminium, die-cast

XCFA 44 C

Mounting: M6S 8×16 (3), BRB 8.4×16 (3), XCAN 8 (3)

Angle bracket, die-cast, 124×80×38



Angle bracket
Aluminium, die-cast

XCFA 44 D

Mounting: M6S 8×16 (5), BRB 8.4×16 (5), XCAN 8 (5)

 © FlexLink 2026

Angle bracket, die-cast, 24×33×22



Angle bracket
Aluminium, die-cast **XCFA 24**

Mounting: MC6S 6×14 (2), BRB 6.4×12 (2), XCAN 6 (2)

Angle bracket, extruded, 90×40×80



Angle bracket
Aluminium, anodized **XCFA 84**

Mounting: M6S 8×16 (6), BRB 8.4×16 (6), XCAN 8 (6)

Angle bracket, extruded, 80×40×40



Angle bracket
Aluminium, anodized **XCFA 44**

Mounting: M6S 8×16 (2), BRB 8.4×16 (2), XCAN 8 (2)

Stay bracket, adjustable



Stay bracket, including reversible guide lugs
Zinc, die-cast **XCFJ 44 F**

Mounting: MLC6S 8×14 (2), XCAN 8 (2) (beam side) or MLC6S 8×30 (2) (beam end)

Stay bracket, fixed, 45°



Stay bracket, 45°
Aluminium, anodized **XCAB 44**

Mounting plate 88×145



Mounting plate
Aluminium, anodized **XCFB 88**

For use with 88×88 mm XCBM beams.
Mounting: M6S 8×18 (4), BRB 8.4×16 (4), XCAN 8 (4), MF6S 8×30 (4).

Mounting plate 44×145



Mounting plate
Aluminium, anodized **XCFB 44×88 A**

For use with 44×88 mm XCBM beams.
Mounting: M6S 8×18 (2), BRB 8.4×16 (2), XCAN 8 (2), MF6S 8×30 (2).

Mounting plate 88×100



Mounting plate
Aluminium, anodized **XCFB 44×88 B**

For use with 44×88 mm XCBM beams.
Mounting: M6S 8×18 (4), BRB 8.4×16 (4), XCAN 8 (4) + MF6S 8×30 (2). Cannot be used with XCBL beams.

Mounting plate 64×120



Mounting plate
Aluminium, anodized **XCFB 64 A**

For use with 64×64 mm XCBM beams.
Mounting: M6S 8×18 (2), BRB 8.4×16 (2), XCAN 8 (2) + MF6S 8×30 (4). Cannot be used with XCBL beams.

Mounting plate 44×120



Mounting plate
Aluminium, anodized **XCFB 44×64 A**

For use with 44×64 mm XCBM beams.
Mounting: M6S 8×18 (2), BRB 8.4×16 (2), XCAN 8 (2) + MF6S 8×30 (4). Cannot be used with XCBL beams.

Mounting plate 64×100



Mounting plate
Aluminium, anodized **XCFB 44×64 B**

For use with 44×64 mm XCBM beams.
Mounting: M6S 8×18 (2), BRB 8.4×16 (2), XCAN 8 (2) + MF6S 8×30 (4).

Mounting plate 44×100



Mounting plate
Aluminium, anodized **XCFB 44**

For use with 44×44 mm beams (not XCBL 3/6/Lx44).
Mounting: M6S 8×18 (2), BRB 8.4×16 (2), XCAN 8 (2) + MF6S 8×30 (1).

T-slot nut for System XC T-slot



T-slot nut for XC
Steel, zinc-chromated

M5, multipack (10 pcs)	**XCAN 5 Q10**
multipack (100 pcs)	**XCAN 5 Q100**
multipack (250 pcs)	**XCAN 5 Q250**
M6, multipack (10 pcs)	**XCAN 6 Q10**
multipack (100 pcs)	**XCAN 6 Q100**
multipack (250 pcs)	**XCAN 6 Q250**
M8, multipack (10 pcs)	**XCAN 8 Q10**
multipack (100 pcs)	**XCAN 8 Q100**
multipack (250 pcs)	**XCAN 8 Q250**

Nut profile for T-slot



Nut profile for T-slot
Length 500 mm
Steel, electro-zinc-plated **XCAP 500**

T-slot connector



T-slot connector
Steel, electro-zinc-plated **XCEC 12**

Parallel connector



Parallel connector assembly
Length 75 mm
Aluminium, anodized **XCFP 75**

Connector for connecting beams T-slot to T-slot

 © FlexLink 2026

T-slot washer kit



T-slot washer kit
Steel, electro-zinc-plated **XCAQ 20 CA**

The kit contains 1 T-slot washer, 1 cap (for ∅ 10 mm hole).
Note. Contains 10 pcs.

T-slot washer strip kit



T-slot washer strip kit
Length 64 mm
Steel, electro-zinc-plated **XCAQ 20×64 CA**

The kit contains 1 T-slot washer strip, 2 caps (for ∅ 10 mm hole)

Fastener yoke 44 mm





Fastener yoke assembly
Length 44 mm
Zinc, die-cast **XCAF 44**

Fastener yoke 64 mm



Fastener yoke assembly
Length 64 mm
Zinc, die-cast **XCAF 64**

Fastener yoke 88 mm



Fastener yoke assembly
Length 88 mm
Zinc, die-cast **XCAF 88**

Drill fixture for fastener yokes and T-slot washer



Drill fixture
Steel, black chromated **XCAD 10/18**

Drill insert ∅ 12,2 mm **18×16 12.2**

The drill fixture is used for fastener yokes (∅ 18,25 mm) and for the T-slot washer (∅ 10 mm)

Square nut M6



Square nut, M6 thread
Steel, electro-zinc-plated **XLAQ 6**

Note. Contains 50 pcs.

Square nut M8



Square nut, M8 thread
Steel, electro-zinc-plated **XLAQ 8**

Note. Contains 50 pcs.

Connecting strip 76 mm



Connecting strip, M8 threads
Length 76 mm
Steel, electro-zinc-plated **XLCJ 5×76**

Contains 10 pcs.

Connecting strip 140 mm



Connecting strip
Length 140 mm
Steel, electro-zinc-plated **XLCJ 5×140**

Contains 10 pcs.

Including M8 set screws

Inner fitting 90°



Inner fitting 90°
Steel, electro-zinc-plated **XMRX 20 A***

Mounting: M6S 8×14 (1), BRB 8.4×16 (1), XCAN 8 (1)
**Note. Contains 10 pcs.*
Including set screw

Inner fitting 90°, double



Inner fitting 90°, double
Steel, electro-zinc-plated **XMRY 20**

Note. Contains 10 pcs.
Including screws

Inner fitting 90°



Inner fitting 90°
Steel, electro-zinc-plated **XMRY 20 A***

Mounting: M6S 8×14 (2), BRB 8.4×16 (2), XCAN 8 (2)
**Note. Contains 10 pcs.*

Inner fitting 90°



Inner fitting 90°
Steel, electro-zinc-plated **XMRY 20 B**

Note. Contains 10 pcs.
Including set screws

Inner fitting 45°



Inner fitting 45°
Steel, electro-zinc-plated **XMRY 20×45 A***

Mounting: M6S 8×14 (2), BRB 8.4×16 (2), XCAN 8 (2)
**Note. Contains 10 pcs.*

 © FlexLink 2026

Corner fitting 90°



Corner fitting 90°
Steel, electro-zinc-plated **XMRW 20**

Note. Contains 10 pcs.
Including set screws

Corner fitting 45°



Corner fitting 45°
Steel, electro-zinc-plated **XMRW 20×45**

Note. Contains 10 pcs.
Including set screws

Feet XC

Foot 44×130



Foot for beam XCBM/XCBL ..x44
Aluminium, die-cast **XCFF 44×130**

Including fastener kit
Maximum bending moment 250 Nm

Foot plate for beam 44×44



Foot plate for beam XCBM/XCBL ..x44
Aluminium, anodized **XCFB 44 F**

Mounting: MF6S 8x30 (1) or MF6S 6x30 (4).
Maximum bending moment 50 Nm

Foot 64×210



Foot for beam XCBM/XCBL ..x64
Aluminium, die-cast **XCFF 64×210**

Including fastener kit
Maximum bending moment 750 Nm

Foot plate for beam 88×88



Foot plate for beam
XCBM/XCBL ..x88
Aluminium, anodized **XCFB 88 F**

Mounting: MF6S 8x30 (4) or MF6S 6x30 (4).
Maximum bending moment 200 Nm

Foot 88×260



Foot for beam XCBM/XCBL ..x88
Aluminium, die-cast **XCFF 88×260**

Including fastener kit
Maximum bending moment 1500 Nm

Adjustable foot M8



Adjustable foot
Steel, electro-zinc-plated
M8 thread **XLFS 8**

Including nut. Maximum vertical load 400 N

Mounting: XCFE 44 M8

Adjustable foot, polyamide, M8



Adjustable foot
PA + steel, electro-zinc-plated
M8 thread

XCFS 8×40×43

Maximum vertical load 12000 N

Mounting: XCFE 44 M8

Polyamide foot, adjustable



Adjustable foot
Stainless steel
M16 thread

XCFS 16×60×115

Including nut
Maximum vertical load 12000 N

Adjustable foot M12



Adjustable foot
Steel, electro-zinc-plated
M12 thread

XCFS 12×68

Including nut. Maximum vertical load 2500 N

Mounting: XCFE .. M12.

Adjustable foot, polyamide, M12



Adjustable foot
PA + steel, electro-zinc-plated
M12 thread

XCFS 12×60×71

Including nut. Maximum vertical load 15000 N

Mounting: XCFE .. M12.

Guide roller



Guide roller
Steel, electro-zinc-plated

XCAG 80 A

Mounting: XCAN 8 or XCFE .. M12
Maximum vertical load 600 N
Including fastener kit

Guide roller with multistop brake



Guide roller with multistop brake
Steel, electro-zinc-plated

XCAG 80 BA

Mounting: XCAN 8 or XCFE .. M12
Maximum vertical load 600 N
Including fastener kit

 © FlexLink 2026

Three-point foot for XC beam



Three-point foot for XC.. 64 beam
D=64 mm
Polyamide, glass-fibre reinforced.

XEFG 64 T

Maximum vertical load 800 N
Including screws and clamps

Three-point foot for XEFU 500



Three-point foot for XEFU 500
D=70 mm
Polyamide, glass-fibre reinforced

XEFG 70 T

Maximum vertical load 800 N
Including screws and clamps

Two-point foot for XC beam



Two-point foot for XC.. 64 beam
D= 64 mm
Polyamide, glass-fibre reinforced

XEFG 64 D

Maximum vertical load 800 N
Including screws and clamps

Adjustable foot for XEFG



Adjustable foot for XEFG 64/70 T/D
Polyamide, glass-fibre reinforced

XLFS 20 P

With ball joint and M20 locking nut.
Maximum vertical load 500 N

Vibration absorber



Vibration absorber for XLFS 20 P
Thermoplastic polyester

XLFJ 69

Height adjustment assembly



Height adjustment assembly for XEFG 70 T
Length 500 mm
Aluminium, anodized

XEFU 500

Square section tube. Including locking levers

End plate for beam 44×44 M8



End plate for beam XCBL ...x44
M8 thread
Zinc, die-cast

XCFE 44 M8

Mounting: MC6S-TT 6x30 (4)

End plate for beam 44×44, M12 thread



End plate for beam XCBL ...×44
M12 thread
Zinc, die-cast

XCFE 44 M12

Mounting: MC6S-TT 6×30 (4)

End plate for beam 44×64



End plate for beam
XCBL/XCBM ...×44×64
M12 thread
Zinc, die-cast

XCFE 44×64 M12A

Mounting: MC6S-TT 6×30 (4)

End plate for beam 64×64



End plate for beam
XCBL/XCBM ...×64
M12 thread
Zinc, die-cast

XCFE 64 M12A

Mounting: MC6S-TT 6×30 (4)

End plate for beam 44×88



End plate for beam
XCBL/XCBM ...×44×88
M12 thread
Zinc, die-cast

XCFE 44×88 M12A

Mounting: MC6S-TT 6×30 (4)

End plate for beam 88×88



End plate for beam
XCBL/XCBM ...×88
M12 thread
Zinc, die-cast

XCFE 88 M12A

Mounting: MC6S-TT 6×30 (4)

Floor attachment bracket



Floor attachment bracket
Stainless steel

XCFA 170 S

The bracket is delivered with the hardware necessary for attachment to the conveyor support. Fasteners for connection to the floor are not supplied with the brackets.

 © FlexLink 2026

Enclosure beam 44×44, two adjacent T-slots



Enclosure beam 44 mm × 44 mm
with two adjacent T-slots
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44 T2**
Length to order (30- 3000 mm) **XCBL L×44 T2**

End cap, polyamide **XCBE 44***

Beam weight: 1,66 kg/m
**Note. Contains 10 pcs.*

Enclosure beam 44×44, two opposite T-slots



Enclosure beam 44 mm ×
44 mm with two opposite T-slots
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44 T2A**
Length to order (30- 3000 mm) **XCBL L×44 T2A**

End cap, polyamide **XCBE 44***

Beam weight: 1,61 kg/m
**Note. Contains 10 pcs.*

Enclosure beam 44×44, three T-slots



Enclosure beam 44 mm ×
44 mm with three T-slots
Lightweight design
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBL 3×44 T3**
Length to order (30- 3000 mm) **XCBL L×44 T3**

End cap, polyamide **XCBE 44***

Beam weight: 1,76 kg/m
**Note. Contains 10 pcs.*

Corner beam



Enclosure beam 44 mm × 44 mm
Corner profile
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBR 3×44**
Length to order (30- 3000 mm) **XCBR L×44**

End cap, polyamide **XCBE 44 R***

Beam weight: 1,91 kg/m
**Note. Contains 10 pcs.*

Corner beam





Enclosure beam 49 mm × 49 mm
Corner profile with slot for 2 mm panel
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBR 3×49**
Length to order (30- 3000 mm) **XCBR L×49**

End cap, polyamide **XCBE 49 R***

Beam weight: 1,77 kg/m
**Note. Contains 10 pcs.*

Matching enclosure profile: XCEP ..x6x44 (see below).

End plate for corner beam XCBR ..×49



End plate
Zinc, die-cast **XCFE 49 R M16**

Mounting to beam end: MC6S-TT 6x30 (2)

Corner beam



Enclosure beam 88 mm × 88 mm
Corner profile
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCBR 3×88**
Length to order (30- 3000 mm) **XCBR L×88**

Beam weight: 3,6 kg/m

Enclosure profile



Profile for 2 mm enclosure panels
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCEP 3×6×44**
Length to order (30- 3000 mm) **XCEP L×6×44**

Mounting: MF6S 6×14, XCAN 6.
Holes (∅6,5 mm) must be drilled in the profile.

Enclosure profile, edge





Profile for enclosures
Aluminium, anodized
Edge profile, Length 3 m (3030 ±5 mm) **XCEP 3×10×44**
Edge profile, Length to order (30- 3000 mm) **XCEP L×10×44**

Mounting: MF6S 6×16 (for 6 mm panels) XCAN 6.
Holes (∅6,5 mm) must be drilled in the profile.
For mounting panels and nets to all standard profiles with a minimum width of 44 mm.

Enclosure profile, inner





Profile for enclosures
Aluminium, anodized
Inner profile, Length 3 m (3030 ±5 mm) **XCEP 3×5×44**
Inner profile, Length to order (30- 3000 mm) **XCEP L×5×44**

Mounting: MF6S 6×16 (for 6 mm panels) XCAN 6.
Holes (∅6,5 mm) must be drilled in the profile.
For mounting panels and nets to all standard profiles with a minimum width of 44 mm.

Profile for sliding door



Profile for sliding door
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XLFL 3**
Length to order (30- 3000 mm) **XLFL L**

Mounting: MLC6S 6×12, XCAN 6 (profile), or MC6S 6×14, BRB 6.4×12 and M6M 6 (angle bracket)

 © FlexLink 2026

Slide strip for sliding doors



Slide strip for sliding doors
Length 3 m
Polyvinyl chloride

XLFR 3

Sliding door profile



Sliding door profile
Length 3 m
Polyvinyl chloride, grey

XCET 3 D

Multiblock



Multiblock, assembly
PA6 + GF

XCAM 14 A

Including clamp and BN2040 5x16 A2K screw
Mounting: clamp(1) and BN2040 5x16 A2K screw (1) or BN2040 5x16 A2K screw (1)
**Note. Contains 10 psc.*

Rubber strip for panels



Rubber strip for panels
Length 25 m
EPDM rubber, black

XCET 25

Rim strip



Rim strip
Length 3 m
Polyvinyl chloride, grey

XCET 3 A

Net strip



Net strip
Polyvinyl chloride, grey
Length 3 m

XCET 3 C

Hinge



Hinge
Polyamide

XCAH 50

Including rotatable guide lugs
Mounting: MLC6S 6x12 (2), XCAN 6 (2)

Hinge kit



Hinge kit
Aluminium, anodized

XCAH 110 A

Including the necessary mounting hardware

Handle assembly XC/XF, polyamide



Handle assembly
Polyamide **XDEH 160**

Mounting: MC6S 5×20 (2), XCAN 5 (2)
Including adapter plate for XC

Ball latch lock kit XC–XC



Ball latch lock kit
Aluminium, anodized **XCEL 60 B**

Including ball latch and the necessary mounting hardware

Ball latch lock kit XC–XC



Ball latch lock kit
Aluminium, anodized **XCEL 60 BA**

Including ball latch and the necessary mounting hardware

Safety switch bracket kit XC–XC



Safety switch bracket kit
Aluminium, anodized **XFEL 60 WA**

Including the necessary mounting hardware. For safety switches Schmersal AZ 15/16-B1 and Guardmaster Trojan 5. Safety switch is not included

Safety switch bracket kit XC–XC



Safety switch bracket kit
Aluminium, anodized **XCEL 60 WA**

Including the necessary mounting hardware
For safety switches Schmersal AZ 15/16-B1 and Guardmaster Trojan 5. Safety switch is not included

Enclosure components XC – conduit elements

Cable duct 22×22 mm



Cable duct, 22 mm × 22 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCD 3×22**
Length to order (30- 3000 mm) **XCCD L×22**

 © FlexLink 2026

Cable duct 44×44 mm



Cover for cable duct, 44 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCC 3×44**
Length to order (30- 3000 mm) **XCCC L×44**

Cable duct, 44 mm × 44 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCD 3×44**
Length to order (30- 3000 mm) **XCCD L×44**

Cable duct 44×88 mm



Cover for cable duct, 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCC 3×88**
Length to order (30- 3000 mm) **XCCC L×88**

Cable duct, 44 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCD 3×44×88**
Length to order (30- 3000 mm) **XCCD L×44×88**

Cable duct 88×88 mm



Cover for cable duct, 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCC 3×88**
Length to order (30- 3000 mm) **XCCC L×88**

Cable duct, 88 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCD 3×88**
Length to order (30- 3000 mm) **XCCD L×88**

Cable duct with divider 88×88 mm



Cover for cable duct, 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCC 3×88**
Length to order (30- 3000 mm) **XCCC L×88**

Cable duct with divider,
88 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCCD 3×88 D**
Length to order (30- 3000 mm) **XCCD L×88 D**

Cable duct 88×88 mm, L-connection 45° and 90° and T-connection



Cable duct, 88 mm L-connection 45° Aluminium, anodized Used with Cable duct 88×88 mm XCCD 3x88 and XCCD 3x88 D	**5116127**
Cable duct, 88 mm L-connection 90° Aluminium, anodized Used with Cable duct 88×88 mm XCCD 3x88 and XCCD 3x88 D	**5116125**
Cable duct, 88 mm T-connection Aluminium, anodized Used with Cable duct 88×88 mm XCCD 3x88 and XCCD 3x88 D	**5120361**

Note! L-connection Incl. 2 pcs of Adapter 5116441. T-connection Incl. 3 pcs of Adapter 5116441

Components for linear motion XC

Sliding element for T-slot



Sliding element for T-slot
Ultra-high molecular weight polyethylene **XCLB 20×30**

Including set screw

Guide profile



Guide profile
Aluminium, anodized
Length 3 m (3030 ±5 mm) **XCLP 3×44**
Length to order (30- 3000 mm) **XCLP L×44**

Mounting: MF6S 6×12, XCAN 6

End cap for guide profile



End cap for guide profile
XCLP ..×44
Polyamide **XCBE 20×44***

Mounting: MLC6S 5×10 (2)
**Note. Contains 10 pcs.*

 © FlexLink 2026

Sliding element for guide profile, polyethylene



Sliding element assembly for guide profile XCLP ..x44
Ultra-high molecular weight polyethylene

XCLE 34×52

Adjustable sliding element for guide profile



Sliding element assembly for guide profile XCLP ..x44
Die-cast aluminium with ultra-high molecular weight polyethylene slide inserts.

XCLE 34×80 A

Can also be mounted with a suitable M6 screw from the outside and an M6M 6 nut

Wheel, diameter 48 mm



Wheel, diameter 48 mm
Polyamide

XCAW 48

Mounting: M6S 8×30 (1), BRB 8.4×16 (1), XCAN 8 (1)
Including bearing and spacer sleeve

Guide wheel, diameter 48 mm



Guide wheel, diameter 48 mm
Polyamide

XCAW 48 G

Mounting: M6S 8×30 (1), BRB 8.4×16 (1), XCAN 8 (1)
Including bearing and spacer sleeve

Wheel yoke



Wheel yoke
Zinc, die-cast

XCAY 44

Mounting: MC6S 8×14 (1) and XCAN 8 (1) (beam side) or MC6S 8×30 (1) (beam end)
Including guide lugs

Saddle for linear beam



Saddle for linear beam
Aluminium, anodized
L = 250 mm
L = 300 mm

XCLZ 250×132
XCLZ 300×220

Including end caps with springs, felt pads, lubrication oil and assembly instructions

Linear beam adapter



Linear beam adapter
Aluminium, anodized
Length 3 m (3030 ±5 mm)
Length to order (30- 3000 mm)

XCLY 3×88×15
XCLY L×88×15

For use with 64 or 88 mm XC beam and steel shaft XCLJ 10×3

Linear beam 68×88 mm



Linear beam 68 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm)
Length to order (30- 3000 mm)

XCLY 3×88×68
XCLY L×88×68

End cap: Use XCBE 44×88 (2), XCBE 15×44 (2)
For use with steel shaft XDLJ 6×3

Steel shaft 6 mm for linear beam



Steel shaft for linear beams
Diameter 6 mm
Length 3 m

XDLJ 6×3

Linear beam 88×88 mm



Linear beam 88 mm × 88 mm
Aluminium, anodized
Length 3 m (3030 ±5 mm)
Length to order (30- 3000 mm)

XCLY 3×88
XCLY L×88

End cap: Use XCBE 88 (2)
For use with steel shaft XCLJ 10×3

Steel shaft 10 mm for linear beam



Steel shaft for linear beams
Diameter 10 mm
Length 3 m

XCLJ 10×3

Components for rotating motion XC

Joint



Joint
Zinc, die-cast

XCFJ 44

Mounting: MLC6S 8×14 (2), XCAN 8 (2) (beam side) or MLC6S 8×30 (2) (beam end)
Including reversible guide lugs

Joint, extruded



Extruded joint for two profiles, T-slot to T-slot
Aluminium, anodized

XCFJ 75 E

Mounting: MLC6S 8×14 (4), XCAN 8 (4)

 © FlexLink 2026