




# Conveyor system WK – links and belts



## Links and plastic rods

The belt consists of plastic hinge-type links connected by plastic rods and locked by plastic snap-in guide clips. The clips also serve as lateral chain guides. See photo.

The belt is woven together by 75 mm and 150 mm wide links. The assembled belt forms a wide, flat and tight conveyor surface. Six standard widths of belt can be delivered, from 150 mm up to 1200 mm. The 900 mm and 1200 mm wide belt come equipped with guide clips at the centre, in addition to those at the edges.



*Belt components*

## Technical characteristics

Belt width	150/225/300/600/ 900 and 1200 mm
Belt weight (Acetal)	10,66 kg/m <sup>2</sup>
Belt pitch	38,1 mm
Max. permissible belt tension	1250 N
Temperature range (Acetal)	-20 °C to +40 °C (Request for quotation other temperatures)


## Tools and accessories

No special tools are required. The belt is lubrication-free. A new belt running on new slide rails, however, will need a few hours of running-in before it runs perfectly smoothly. For applications where absolutely smooth running is essential from start, use a silicone or teflon based lubricant.

## Ordering information


The belt is delivered in assembled 1 m lengths one plastic rod and two guide clips are included. To calculate the total length required, remember to add for belt consumed by the idler and drive units.

**Belt direction** (not applicable for center guide WK900)



Introduction  
X45  
X45H  
XS  
XL  
X65  
XM  
X70X  
X85  
X85X  
XH  
XK  
X180  
X180X  
X300  
X300X  
XT  
XTC  
WK  
WL  
WL 222X  
WL 273X  
WL 374X  
WL 526X  
WL 678X  
ELV  
IDX


## Belts 150 mm



Belt 150 mm  
Length 1 m (POM A)  
Chain link 150 mm

**WKTP 1B150**  
**WKTL 150**


## Belts 900 mm



Belt 900 mm  
Length 1 m (POM A)  
Chain link 75 mm  
Chain link 150 mm

**WKTP 1B900**  
**WKTL 75**  
**WKTL 150**


## Belts 225 mm



Belt 225 mm  
Length 1 m (POM A)  
Chain link 75 mm  
Chain link 150 mm

**WKTP 1B225**  
**WKTL 75**  
**WKTL 150**


## Belts 1200 mm



Belt 1200 mm  
Length 1 m (POM A)  
Chain link 75 mm  
Chain link 150 mm

**WKTP 1B1200**  
**WKTL 75**  
**WKTL 150**


## Belts 300 mm



Belt 300 mm  
Length 1 m (POM A)  
Chain link 75 mm  
Chain link 150 mm

**WKTP 1B300**  
**WKTL 75**  
**WKTL 150**


## Belts rod



Belt rod  
Length 3 m (PA66)

**WKTD 5x3000 P**


## Belts 600 mm



Belt 600 mm  
Length 1 m (POM A)  
Chain link 75 mm  
Chain link 150 mm

**WKTP 1B600**  
**WKTL 75**  
**WKTL 150**

## Belts guide clip



Belt guide clip, right  
Belt guide clip, left

**3904683**  
**3904684**